

SMART POWER CABLE: RG32-5S5S



Voltage: 415/240V 3Ø Wye
 Amperage: 32A
 Plug: IEC 60309 532P6S
 Connector: IEC 60309 532C6S

PLUG: IEC 60309 532P6S	CONNECTOR: IEC 60309 532C6S

Smart Power Cable with in-line wireless power monitoring.

For use on a 32A 415/240V three-phase (3Ø) Wye circuit with circuit protection.

Radio zone must be set to the region where the cable will be used. Packet Power Ethernet Gateway required to receive data from Smart Power Cable.

SPECIFICATIONS

Voltage	415/240V 3Ø Wye
Amperage	32A (rated at 25A)
Frequency	50 to 60 Hz
Male Plug	IEC 60309 532P6S, 4 Pole, 5 Wire grounding, IP44
Female Connector	IEC 60309 532C6S, 4 Pole, 5 Wire grounding, IP44

Connector Type	Pin and sleeve
Cable Wire Gauge	4mm ²
# of Wires	5
Wire Colors	Brown/Black/Gray/Blue/Green
Cord Type	H07RN-F 5G4.0
Standard Cable Length	1.5 m (59 in)
Weight	1.7 kg (3.7 lbs)
Monitoring Unit Housing	Single die cast aluminum gang box housing Packet Power transmitter extending 1/2 inch off top of box: 114 x 70 x 83mm (4.5 x 2.75 x 3.25 in)
IP Rating	Not rated; IP44 available at an added cost
Power Monitoring	3Ø Wye: L1-N and L2-N and L3-N: V, A, VA, W, Wh, power factor; aggregate: W, Wh, frequency
Power Usage	0.6W used for monitoring
Temperature Monitoring	-7°C to 45°C (20°F to 113°F); ±2°C
Circuit Protection	None
Wireless Network Protocol	Frequency hopping self-configuring load-balancing mesh; Operating frequency 860 to 930 MHz and 2.4 GHz (frequencies vary by region)
Wired Network Protocols	HTTPS to Packet Power EMX running locally or as cloud service; SNMP V1/V2c/V3; Modbus TCP/IP
LED Indicator Lights and Display	BLUE (powered on), RED (seeking wireless communication), GREEN (wireless communication activity); 3 digit LED (cycles Amps and Volts by phase)
Made in USA	Yes
Product Warranty	1 year
Certifications	UL/ANSI 61010-1, CSA 61010-1. IEC 61010-1:2001 and EN 61010-1:200. AS/NZS 4268: 2008. EU R&TTE ETSI EN 300 220-2 and ETSI EN 301 489-3, CENELEC EN 61326-1; IEC 61326-1:2005;;1997. FCC Class B device