


SMART POWER CABLE: RG50-8365



Voltage: 240V 3ØΔ
 Amperage: 50A
 Plug: CS8365
 Connector: CS8364

PLUG: CS8365	CONNECTOR: CS8364
	

Smart Power Cable with in-line wireless power monitoring.

For use on a 50A 240V three-phase delta (3ØΔ) circuit with circuit protection.

Radio zone must be set to the region where the cable will be used. Packet Power Ethernet Gateway required to receive data from Smart Power Cable.

SPECIFICATIONS

Voltage	240V 3ØΔ
Amperage	50A (rated at 45A)
Frequency	50 to 60 Hz
Male Plug	CS8365, 3 Pole, 4 Wire grounding, IP44
Female Connector	CS8364, 3 Pole, 4 Wire grounding, IP44

Connector Type	Twist lock
Cable Wire Gauge	6 AWG
# of Wires	4
Wire Colors	Black/Red/White/Green
Cord Type	STO 600V 105C
Standard Cable Length	1.1 m (44 in)
Weight	2.3 kg (5 lbs)
Monitoring Unit Housing	Double die cast aluminum gang box housing Packet Power transmitter extending 1/2 inch off top of box: 114 x 114 x 83mm (4.5 x 4.5 x 3.25 in)
IP Rating	Not rated
Power Monitoring	3ØΔ (2-element monitoring): L1: A, L2: A, L3: A, L1-L3: V, VA, W, Wh, power factor; L2-L3: V, VA, W, Wh, power factor; L1-L2: V; aggregate: W, Wh, frequency
Power Usage	0.6W used for monitoring
Temperature Monitoring	-7°C to 45°C (20°F to 113°F); ±2°C
Circuit Protection	None
Wireless Network Protocol	Frequency hopping self-configuring load-balancing mesh; Operating frequency 860 to 930 MHz and 2.4 GHz (frequencies vary by region)
Wired Network Protocols	HTTPS to Packet Power EMX running locally or as cloud service; SNMP V1/V2c/V3; Modbus TCP/IP
LED Indicator Lights and Display	BLUE (powered on), RED (seeking wireless communication), GREEN (wireless communication activity); 3 digit LED (cycles Amps and Volts by phase)
Made in USA	Yes
Product Warranty	1 year
Certifications	UL/ANSI 61010-1, CSA 61010-1, IEC 61010-1:2001 and EN 61010-1:200. AS/NZS 4268: 2008. EU R&TTE ETSI EN 300 220-2 and ETSI EN 301 489-3, CENELEC EN 61326-1; IEC 61326-1:2005;:1997. FCC Class B device